

Please amend the application as follows:

In the Claims

Please cancel Claims 37 and 38.

Please amend Claims 14, 17, 25-29, 39. Amendments to the claims are indicated in the attached "Marked Up Version of Amendments" (pages i - ii)

14. (Five Times Amended) A portable display system, comprising:
- a housing;
 - a matrix display mounted to the housing, the matrix display including an array of pixel electrodes and a counterelectrode separated by a liquid crystal material, the matrix display having a display area of less than about 200 mm²;
 - a light source that flashes to illuminate the matrix display;
 - a display control circuit coupled to the matrix display and the light source to actuates the pixel electrodes and the light source to display an image for viewing, the display control circuit including:
 - a switching circuit that switches a common voltage applied to the counterelectrode to erase any displayed image; and
 - a timing circuit that determines when the display control circuit actuates the pixel electrodes to render an image, when to flash the light source to illuminate the image, and when the switching circuit switches the common voltage applied to the counterelectrode to erase the image; and
 - a lens that magnifies the image on the matrix display
17. (Twice Amended) The portable display system of claim 14 wherein the array of pixel electrodes comprises an array of at least 640 x 480 pixel electrodes.
25. (Twice Amended) The portable display system of claim 14 further comprising an electronic card reader that receives the video input from an electronic card.

- F3
CWE
26. (Twice Amended) The portable display system of claim 25 wherein the electronic card reader interfaces with at least one of a memory card or a smart card.
27. (Twice Amended) The portable display system of claim 14 wherein the active matrix display is a color sequential display.
28. (Amended) The portable display system of claim 14 wherein the array of pixel electrodes comprises an array of at least 320 x 240 pixel electrodes.

- F4
29. (Amended) The portable display system of claim 14 wherein the matrix display further comprises an array of transistor circuits formed with single crystal silicon, the array of transistor circuits being bonded to an optically transmissive substrate with an adhesive layer.

- F5
39. (Amended) The portable display system of claim 14 wherein the common applied voltage is a high or a low common voltage selected by the switching circuit.

Please add new Claims 40 - 58.

40. (New) The portable display of claim 14 wherein the matrix display is an active matrix display.
41. (New) A portable display system, comprising:
- a matrix display mounted to the housing, the matrix display including an array of pixel electrodes and a counterelectrode separated by a liquid crystal material, the matrix display having a display area of less than about 200 mm²;
 - a light source that flashes to illuminate the matrix display;
 - a display control circuit coupled to the matrix display and the light source to actuates the pixel electrodes and the light source to display an image for viewing, the display control circuit including:
- F6

a switching circuit that switches a common voltage applied to the counterelectrode to erase any displayed image; and

a timing circuit that determines when the display control circuit actuates the pixel electrodes to render an image, when to flash the light source to illuminate the image, and when the switching circuit switches the common voltage applied to the counterelectrode to erase the image.

42. (New) The portable display system of claim 41 wherein the light source is a light emitting diode device.
43. (New) The portable display system of claim 41 wherein the array of pixel electrodes comprises an array of at least 640 x 480 pixel electrodes.
44. (New) The portable display system of claim 41 further comprising an electronic card reader that receives the video input from an electronic card.
45. (New) The portable display system of claim 44 wherein the electronic card reader interfaces with at least one of a memory card or a smart card.
46. (New) The portable display system of claim 41 wherein the active matrix display is a color sequential display.
47. (New) The portable display system of claim 41 wherein the array of pixel electrodes comprises an array of at least 320 x 240 pixel electrodes.
48. (New) The portable display system of claim 41 wherein the matrix display further comprises an array of transistor circuits formed with single crystal silicon, the array of transistor circuits being bonded to an optically transmissive substrate with an adhesive layer.

F6
Cont

49. (New) The portable display system of claim 41 wherein the common applied voltage is a high or a low common voltage selected by the switching circuit.
50. (New) The portable display system of claim 41 wherein the matrix display is an active matrix display.
51. (New) A portable display system, comprising:
- an active matrix display mounted to the housing, the active matrix display including an array of pixel electrodes and a counterelectrode separated by a liquid crystal material, and an array of transistor circuitss formed from single crystal silicon for actuating the pixel electrodes, the active matrix display having a display area of less than about 200 mm²;
 - a light source including a light emitting diode that flashes to illuminate the active matrix display;
 - a display control circuit coupled to the active matrix display and the light source to actuates the pixel electrodes and the light source to display an image for viewing, the display control circuit including:
 - a switching circuit that switches a common voltage applied to the counterelectrode to erase any displayed image; and
 - a timing circuit that determines when the display control circuit actuates the pixel electrodes to render an image, when to flash the light source to illuminate the image, and when the switching circuit switches the common voltage applied to the counterelectrode to erase the image.
52. (New) The portable display system of claim 51 wherein the array of pixel electrodes comprises an array of at least 640 x 480 pixel electrodes.
53. (New) The portable display system of claim 51 further comprising an electronic card reader that receives the video input from an electronic card.

F6
Cont